


THIS DRAWING AND THE DATA DISCLOSED HEREIN OR HEREWITH IS NOT TO BE REPRODUCED USED OR DISCLOSED IN WHOLE OR IN PART TO ANYONE WITHOUT THE PERMISSION OF JESS-LINK PRODUCTS CO.,LTD.(JPC)

CUSTOMER DRAWING
DRWC-XXXXXX


REV.	ECN NO.	DESCRIPTION	MDF'D	APP'D	DATE
01		INITIAL DESIGN	Philip	Richard	07/12/2023
02					
03					

2X
M12 SHIELLD MALE
8 POSITION X-CODED


5000⁺⁵⁰₋₀



FIELD BUS CABLES - DRAG-CHAIN HIGH SPEED; OUTER SHEATH PUR, UL STYLE 20236 80° C/30V. CAT.5E S/FTP
TWISTED PAIRS, 4X2X26AWG WITH NON-WOVEN TAPE INSERT, CONDUCTOR EXTRA FLEXIBLE BARE COPPER, INSULATION POLYETHYLEN
SHIELD: AL/PET TAPE + TINNED COPPER BRAID O.C. ≥ 85%
SEPARATOR EASY STRIP-AWAY TAPE
OUTER SHEATH PUR, COLOR GREEN / RAL6018



FRONT VIEW



FRONT VIEW

WIRE LIST		
P1		P2
1	WHITE/ORANGE	1
2	ORANGE	2
3	WHITE/GREEN	3
6	GREEN	6
7	WHITE/BLUE	7
8	BLUE	8
5	WHITE/BROWN	5
4	BROWN	4
Shell	BRAID	Shell

NOTES:
MATERIAL:
CONNECTOR: M12 X-CODE MALE
HOUSING:PBT UL94V-0 BLACK
CONTACT: BRASS, 10 MICRO INCHES MIN. GOLD FLASH
NUT: BRASS, NICKEL PLATED
SHELL: ZN ALLOY, NICKEL PLATED
BACK SHELL: BRASS, NICKEL PLATED

MOLDING HOOD: POLYVINYL CHLORIDE(PVC), BLACK

ELECTRONIC:
RATED VOLTAGE: 30V
RATED CURRENT: 0.5A

APPLICATION:
WATER PROOF IS IP67(MATED)

ENVIRONMENTAL:
OPERATING TEMPERATURE RANGE: -40°C TO 80°C (DYNAMIC)
CABLE JACKET RESISTANCE: OIL, FLAME, HALOGEN FREE
CABLE FILEX LIFE: 10 MILLION CYCLE TEST (6.5X CABLE OD))

TESTING CONDITION:
CONDUCTIVE RESISTANCE 2 Ohm Max.
INSULATION RESISTANCE 20M Ohm Min
WITH DC200V DURING 0.05second.

RoHS COMPLIANT	Unit:mm(inch)	PROJECTION 	ZCables.com		
	GENERAL TOLERANCES: (UNLESS SPECIFIED) 0 =±1 (0.039) 0.0 =±.5 (0.02) 0.00 =±.3 (0.012) 0.000=±.15(0.006) 0° =± 2° 0.0° =± 1°	D.R. 07/12/2023 Philip			TITLE M12 X-code 8pin Male MotionBUS Industrial Ethernet CAT.5e Cable
	APV.D 07/12/2023 Richard	SCALE 1:1	SIZE A4	PART NO. PZBJKD050-0003	REV. 01
					SHEET 1 OF 1